


TECHNICAL DATASHEET

REFERENCE: E2221+E2321

Old référence :





ALUMINIZED JACKET AND TROUSERS



Dimensions: 90cm

Sizes availaible S M L XL XXL XXXL

protection against thermal risks (flame, radiant heat and molten metal spraying) -attention it takes a while to remove the pants, in case of significant projections, preferably use a faster coat to remove

The materials of this article do not contain any substance that can harm the health of the user

This PPE is in conformity with the requirements of the Directive 89/686/CEE. PPE class III, AET N°033/2015/0998CENTEXBEL

The CE marking on these items means the respect for the essentials requirements of European Directive on PPE based on the standard EN 340



A1 B1 C4 D3 E3 F1

A Limited flame spread **B** Convective Heat (1 à 3) C Radiant Heat (1 à 4) D Projection of molten aluminium (1 à 3) E Projection of molten iron (1 à 3) **F Contact Heat** (1 à 3)

ISO 11612

Use only within the risks covered above






A dirty clothe may cause a reduced protection/

no washing recommended, clean with a wet sponge or brush, after use, stoker the garment turned over for drying on the inside

Storage: Protected from the light and in a dry place, free of moisture, oils, greases...

Recommandation:

to ensure optimal protection, this equipment must be supplemented with appropriate PPE (trousers, gaiters, gloves, hood, IR



Coat/Apron

•			
Lenght	Α	Sizes	B et C
120 cm	164-170 cm	S – T2	92-96 cm
130 cm	170-182 cm	M – T3	96-104 cm
140 cm	182-188 cm	L – T4	104-112 cm
150 cm	188-194 cm	XL – T5	112-120 cm
160 cm	194-200 cm	XXL – T6	120-128 cm

For coveralls, take the greatest size between B or C. The measures must be taken on the person wearing his work clothes, because this equipment is worn over. In doubt between two sizes choose the larger one.