



TECHNICAL DATASHEET

REFERENCE : **E5121-2A1**

Old référence :

Description :

Made of soft aluminized fleece. Clear visor 300x500mm + hemmed mesh visor in the foreground on arch, not liftable. All seams Kevlar thread



Aluminized Hood

Dimensions :

Sizes available unique

Head protection against thermal risks

Recommandation

The materials of this article do not contain any substance that can harm the health of the user

This PPE is in conformity with the requirements of the (UE) 2016/425.
EPI de catégorie 3, (AET) N°033/2021/0842CENTXBEL

The CE marking on these items means the respect for the essentials requirements of European Directive on PPE based on the standard ISO 13688



A1B1C4D3E3F2

ISO 11612

- A** Limited flame spread
- B** Convective Heat (1 à 3)
- C** Radiant Heat (1 à 4)
- D** Projection of molten aluminium (1 à 3)
- E** Projection of molten iron (1 à 3)
- F** Contact Heat (1 à 3)

Use only within the risks covered above

Maintenance :



A dirty clothe may cause a reduced protection/ no recommended washing, clean with a damp sponge

Storage : Protected from the light and in a dry place, free of moisture, oils, greases...

Recommandation : This equipment must be supplemented by appropriate PPE (aluminized coat, gaiters, gloves, etc.).

Coat/Apron		Sizes	B et C
Lenght	A	S – T2	92-96 cm
120 cm	164-170 cm	M – T3	96-104 cm
130 cm	170-182 cm	L – T4	104-112 cm
140 cm	182-188 cm	XL – T5	112-120 cm
150 cm	188-194 cm	XXL – T6	120-128 cm
160 cm	194-200 cm		

For coveralls, take the greatest size between **B** or **C**. The measures must be taken on the person wearing his work clothes, because this equipment is worn over. In doubt between two sizes choose the larger one.